

Part Number (Артикул)	Description (Описание)
<b>Оптические мультисервисные мультиплексоры</b>	
RCMS2101-30-FV35	Standalone, Optical modem, remote SNMP-management, 1 V.35 interface and 1 10/100M RJ45 port, AC 115V or 230V/DC -48V
RCMS2104-120	Standalone, Optical multiplexer, remote SNMP-management, 4 E1 ports and 4 10/100 RJ45 ports, AC 115V or 230V/DC -48V
RCMS2104-240	Standalone, Optical multiplexer with 2 expansion slots, remote SNMP-management, Maximum capability of configuration: 8 E1 ports and 4 10/100 RJ45 ports, AC 115V or 230V/DC -48V
RCMS2201-30	Module, Optical multiplexer, SNMP-management, 1 E1 port and 1 10/100M port
RCMS2204-240	Module, Optical multiplexer, SNMP-management, 8 E1 ports and 4 10/100M RJ45 ports
RCMS2301-30-FV35	Standalone, Optical modem, 1 V.35 interface and 1 10/100M RJ45 port, remote SNMP-management, SSF, Dual WL 1310nmTX 1550nmRX, AC 115V or 230V/DC -48V
RCMS2304-120	Standalone, Optical multiplexer, 4E1 ports and 4 10/100 RJ45 ports, remote SNMP-management, SSF, Dual WL 1310nmTX 1550nmRX, AC 115V or 230V/DC -48V
RCMS2304-240	Standalone, Optical multiplexer with 2 expansion slots, Maximum capability of configuration: 8 E1 ports and 4 10/100 RJ45 ports, remote SNMP-management, SSF, Dual WL 1310nmTX 1550nmRX, 19" 1U chassis, AC 115V or 230V/DC -48V
RCMS2401-30	Module, Optical multiplexer, SNMP-management, 1 E1 port and 1 10/100M port, SNMP-management, SSF, Dual WL 1310nmTX 1550nmRX
RCMS2404-240	Module, Optical multiplexer, SNMP-management, 8 E1 ports and 4 10/100M RJ45 ports, SNMP-management, SSF, Dual WL 1310nmTX 1550nmRX
RCMS2501-30-FV35	Standalone, Optical modem, 1 V35 interface and 1 10/100M RJ45 port, SNMP-management, SSF, Dual WL 1550nmTX 1310nmRX, AC 115V or 230V/DC -48V
RCMS2504-120	Standalone, Optical multiplexer, 4E1 ports and 4 10/100 RJ45 ports, SNMP-management, SSF, Dual WL 1550nmTX 1310nmRX, AC 115V or 230V/DC -48V
RCMS2504-240	Standalone, Optical multiplexer with 2 expansion slots, Maximum capability of configuration: 8 E1 ports and 4 10/100 RJ45 ports, SNMP-management, SSF, Dual WL 1550nmTX 1310nmRX, 19" 1U chassis, AC 115V or 230V/DC -48V
RCMS2601-30	Module, Optical multiplexer, SNMP-management, 1 E1 port and 1 10/100M port, SNMP-management, SSF, Dual WL 1550nmTX 1310nmRX
<b>Модули расширения оптических мультисервисных мультиплексоров серии RCMS2104-240, RCMS2304-240 и RCMS2504-240.</b>	
SUBM-E	Expansion module 10Base-T port
SUBM-4E1	Expansion module 4 E1 ports
SUBM-FV35	Expansion module 1 V.35 port

**Примечание**

По умолчанию оптический порт RC80X - S1, дальность передачи S1 составляет от 0 до 25км. Дальность передачи может быть увеличена согласно желанию заказчика. Модификация S2 предоставляет дальность передачи от 10 до 60км, а S3 от 15 до 120км.